

Alura Trailer - 3 Axles / Flat-bed Trailer

Document is given with price quotation No: 3512

Technical specifications of 3 axles flat-bed semi trailer – Twin Tyres 40 Ton (Made of ST-52 Steel)

Dimensions :

Length : 12.480 mm

Width : 2.550 mm

Chassis : Its made from ST-52 and made of high resistant universal beam– 457 X 191 X 89 kg

Axles : 3 X 12 T OSMAN KOC brand high quality axles with TUV certificate.

Suspension : Spring (mechanical) suspension on the 3 axles

Brake system : 2 Line air brake system

King-pin : OMS brand 3 ½ " with its protection cover

Landing Legs : OMS brand 24 ton double speed mechanic landing legs and it has TUV certificate. Air spring heavy duty type. 2 units at front

Twist locks : 8 units twist lock and they have TUV certificate.

Wheel and tyres : 12 R 22.5 1st grade 12 + 1 units tyres and rims with TUV certificate

Electrical System : SABA brand 24 V electrical system with side lamps led every 2.5 Meter – It has ADR certificate

Connectors 15 and 7 pin – 2 unit stop lamp by 7 functionally shall be covered with cage installed by bolts.

2 units import plate illumination lamp

Reflectors and velocity plates (with red and white crosses)

Rear lamps have steel protection and it can be opened and closed. Rear side lamps will be placed top of bumper.

Paint : Sandblasting to SA 2 ½ - One coat of primer plus to layer of synthetic finish paint according to customer requirement.

Accessories :

- 2 units projectors
- Lashing rings
- Ro-ro rings
- Bumper and number plate frame.
- Spare tyre frame with locking system
- Toolbox
- Water tank
- 6 units mudguards
- Fire extinguisher box
- Small box for licenses
- 2 units rubber chocks at the rear of trailer
- Reverse alarm system / necessary signposts