

TECHNICAL SPECIFICATIONS FOR BULK CEMENT TRAILER – 30 CBM

Volume : 30 CBM
Material : ST37
Type : V type
Thickness : 4 mm
Working Pressure : 2 Bar
Test Pressure : 2.6 Bar
Discharge Pressure : 2000 ltr/min

TANK EQUIPMENT;

Air compressor with electrical engine
2 Unit Manhole cover (420 mm Diameter)
1 Unit Cement discharge ball valve
1 Unit Air pressure manometer
1 Unit Accelerated ball jet air valve
1 Unit 4" Discharge system
1 Unit Emergency valve for protected to 2.5 bar
Import hose system for making discharge easy

RUNNING GEAR;

Air suspension
Load adjusting valve. Double line brake system with EBS
Automatic brake adjuster
3 Units tire mat
3 Units X 9 Ton capacity – KOC brand high quality drum brake axles.
Tyres & Rims 385 65 R 22.5 6+1 tyres

ACCESSORIES;

1 Unit 6 mt 4" discharge hose
Walking platform
2 Unit inside tool box
Rare access ladder
1 Unit double speed landing leg
2" removeable king-pin

ELECTRICAL SYSTEM

In accordance with EU regulations
24 Volt Electrical system
2 Unit 7 functional stop lamp
4 Unit Number plate lamp
4 Unit Side signal light
Reflectors