

Lubrication Systems



www.aluratrailer.com

sales@aluratrailer.com

Export: +905442420491

COOLANT PUMP



		RAASM / ITALY	
Flow rate		20	l/min
Ratio		3:1	
Compatible fluids		water / coolant	
Suction tube upper body		carbon steel	
Suction tube		G 1/4"	F
Air inlet connection		G 1/2"	F
Fluid outlet connection		4 ÷ 8	
Air working pressure		350	bar
Average air consumption		81	l/min
Max deliverable oil viscosity		130	SAE
Suitable for drums or tanks		modular	
Weight		5,35	kg

HOSE REEL



		RAASM / ITALY	
Pressure		150	bar
Hose length		15	Mt.
Hose Ø		1/2"	Ø
Compatible fluids		oils and similar products	
Seals		polyurethane	
Characteristic		fixed	
Material		painted steel with ABS drum	
Inlet		G 1/2"	F
Outlet		G 1/2"	M
Reel flow path		zinc plated steel	
Internal drum width		140	mm

GUNS FOR DISPENSING



		RAASM / ITALY	
Grip		technopolymer	
Terminal		flexible	
Drip-catcher		automatic ø 16 mm	
Inlet swivel joint		G 1/2"	F
Filter		yes	
Level locking button		yes	

TANK



		ALURA / TURKEY	
Materiel		LDPE	
Capacity		250	lt.
Connection Adapters		yes	