Lubrication Systems



www.aluratrailer.com

sales@aluratrailer.com Export: +905442420491

OIL PUMP



	RAASM /	/ ITALY
Ratio	50:1	
Flow rate	4400	g/min
For drums with internal ø	550 ÷ 600	mm
Weight	38	kg

HOSE REEL



	RAASM /	' HAL
Pressure	400	bar
Hose length	15	Mt.
Hose Ø	3/8"	Ø
Compatible fluids	grease	
Seals	polyurethane	
Characteristic	fixed	
Material	painted steel with ABS drum	
Inlet	G 3/8"	F
Outlet	G 1/4"	М
Reel flow path	zinc plated steel	
Internal drum width	140	mm

GUNS FOR DISPENSING



	RAASM /	/ ITALY
Flow rate	1500	g/min
Ratio	50:1	
Compatible fluids	ases, medium/high viscosity	
Air inlet connection	G 1/4"	F
Fluid outlet connection	G 3/8"	F
Air working pressure	6 ÷ 8	bar
Average air consumption	330	l/min
Noise level	81	dB
Air max pressure	8	bar
Suitable for drums	180 ÷ 220	kg
Weight	6,7	kg

GUNS FOR DISPENSING



Terminal flexible Inlet swivel joint single G 1/4" F Grease coupler special 4-jaw, Grease gun with flexible terminal 400 mm single swivel joint.

RAASM / ITALY